

Aqua-InkClean 2702



PROPERTIES

Mildly alkaline, water-miscible cleaner concentrate for rinsing ink systems after heating and removing residues of water-based inks.

- Single-phase, mildly alkaline concentrate.
- Possesses good dirt-removing properties.
- Designed for removing water-based paints.
- Well suited for cleaning in closed spray processes.
- Product concentration in water should have 5 - 25%.
- Suitable for steel, stainless steel, ceramic, HDPE and Teflon surfaces.
- The working solution should be used in the temperature range of 50 °C - 80 °C.

Characteristic	
Appearance	brown-yellow liquid
Density	approx. 1,332g/l
pH	12 -13
Boiling point	undefined
Flash point	>95°C
Packaging	canister 26kg

APPLICATION

Aqua-InkClean 2702 is a mildly alkaline cleaner concentrate used to produce aqueous cleaning baths for closed cleaning methods using spray applications. **Aqua-InkClean 2702** is designed for removing water-based paints. The good dirt-removing properties of the formulation deserve special mention. In addition, special mention should be made of the single-phase appearance, in the application concentration too. In the application concentration, the cleaning bath is foam-free at temperatures above 40 °C.

PROCESS & NOTES

The optimal cleaning temperature and cleaning bath concentration depend on the degree of difficulty of the cleaning task. This can be determined individually. Maintenance of the cleaning bath is recommended in order to conserve the cleaning effect of the used cleaning bath as long as possible. More detailed information is available on request. To compensate cleaning bath evaporation and entrainment, periodic or continuous topping up of the used cleaning bath with a mixture is recommended. Cleaned surfaces are to be rinsed with water. In the case of standard steel, additional treatment with a temporary anti-corrosion product (e.g. InCorr 2238) is recommended to avoid rust formation. Check aluminium, zinc, non-ferrous metals and plastics for resistance prior to treatment. Protect against frost during storage. Before use, please observe the instructions on personal protection equipment in the safety data sheet.

When using highly effective cleaning agents for industrial applications, special precautions must be taken, and health and safety regulations must be followed. The required personal protective equipment should be used during application, and after completion, hands and work materials should be thoroughly washed. The product should only be stored in its original packaging, which must be disposed of according to the instructions on the safety data sheet after it is emptied. Familiarize yourself with the hazards and safety rules on the label and the safety data sheet, which is available upon request.