FLEKSO
SERWIS

CeraClean® C-22

PRODUCT DESCRIPTION

Aerosol preparation for cleaning injection molds and removing old paint coatings. Highly effective agent for eliminating difficult to remove dried coatings from various surfaces.

TECHNICAL DATA	
Appearance	colorless aerosol
Relative density in 20°C, g/cm3	1,32 ± 0,05
pH	not specified
Boiling point	-42- -1°C (propane/butane)
Flash point	-95- -60°C (propane/butane)
Package	can 400ml

APPLICATION

It is mainly used to clean the surface of dried varnish-like substances, e.g. two-component varnishes.

INTENDED USE

Spray ***CeraClean® C-22*** evenly onto objects at a distance of 30 cm. Use at room temperature with good room ventilation.

When using highly effective cleaning agents for industrial applications, special precautions must be taken, and health and safety regulations must be followed. The required personal protective equipment should be used during application, and after completion, hands and work materials should be thoroughly washed. The product should only be stored in its original packaging, which must be disposed of according to the instructions on the safety data sheet after it is emptied. Familiarize yourself with the hazards and safety rules on the label and the safety data sheet, which is available upon request.

Our knowledge in care of your **print**

Flekso Serwis Sp. z o.o.
NIP 585 13 65 632
ul. Budowlanych 64B, 80-298 Gdańsk
biuro@fleksoserwis.pl
tel. (58) 555 05 22
www.fleksoserwis.pl

Sąd Rejonowy Gdańsk-Północ w Gdańsku,
VII Wydz. Gosp.
KRSKRS 0000123620
REGON 192036339
Kapitał zakładowy 50.000 zł.
BDO 000085139