

KLISHEE SPRAY

PRODUCT DESCRIPTION

Product for efficacious preventing residues of adhesives.

General appearance and composition:

- Mixture of solvents with special agents.
- Colourless and fat free.
- Makes the exchanging of clichés easier.
- Aerosol over head sprayable.

TECHNICAL DATA

Appearance	colorless aerosol
Relative density in 20°C, g/cm ³	0,86
Flammability	extremely flammable
Boiling point	-42°C
Flash point	-97°C
Autoignition temperature	does not spontaneously ignite
Explosive limits	13,0% obj. / 1,5% obj.
Solubility	does not mix or mixes poorly with water
Package	can 500ml

APPLICATION

Klishee Spray is used on printing plates, photopolymers and rubber-cylinders to avoid adhesives after printing run.

INTENDED USE

Spray a thin, even layer of Klishee Spray on the back of the cliché. Allow to dry for approx. 10 minutes. Press Cliché on the cliché-foil. Use at room temperatures in well-ventilated areas.

Attention! Product should be kept for a minimum of 4 years, stored at room temperature.

When using highly effective cleaning agents for industrial applications, special precautions must be taken, and health and safety regulations must be followed. The required personal protective equipment should be used during application, and after completion, hands and work materials should be thoroughly washed. The product should only be stored in its original packaging, which must be disposed of according to the instructions on the safety data sheet after it is emptied. Familiarize yourself with the hazards and safety rules on the label and the safety data sheet, which is available upon request.

1/1