

DOUBLE-SIDED ADHESIVE NON-WOVEN TAPE FS 391030

PRODUCT DESCRIPTION

Double-sided adhesive tape on a cellulose non-woven carrier, coated on both sides with high-quality acrylic adhesive.

APPLICATION

Tape for splicing and laminating paper/foil, used primarily in the production of corrugated cardboard and in foil processing.

PROPERTIES

Technical data	
Carrier	cellulose nonwoven fabric
Carrier color	translucent
Liner	siliconized paper
Liner color	white
Total thickness	0,090 [mm]
Adhesive (inside)	acrylic
Adhesive (outside)	acrylic
Adhesion to steel (inside)	450 cN/cm
Adhesion to steel (outside)	450 cN/cm
Temperature resistance	200 °C

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging in a dry and clean area until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Life expectancy can vary with temperature and humidity: a maximum of 24 months is recommended from the date of manufacturing when product is stored at 22°C +/- 2°C and RH at 50% +/- 5%. Applying surfaces must be dry, free from dust, grease or other surfaces contaminants.

The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Manufacturer expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Manufacturer does not exclude liability for death or personal injury arising from its negligence or fraud.